


K-W90 AG-K O OR

Male elbows, conical male thread (without O-ring)

HANSA FLEX

Karakteristike

| | |
|-----------------------|----------------|
| maks. radni tlak | 18 bar |
| upotreblijiva crijeva | PA, PE, PU |
| Materijal | poniklani mjed |



Napomena

Drugi podatci na zahtjev.

Artikli

| Naziv | Navoj | za crijevo | L1 (mm) | L2 (mm) | SW (veličina ključa) |
|----------------|-------|---------------|------------|------------|----------------------|
| K- 07 40 33 88 | R 1/8 | 6 mm / 4 mm | 22,5 | 17,0 | 8 mm |
| K- 07 40 33 89 | R 1/8 | 8 mm / 6 mm | 22,5 | 17,0 | 10 mm |
| K- 07 40 33 87 | R 1/8 | 10 mm / 8 mm | 25,5 | 18,5 | 11 mm |
| K- 07 40 33 85 | R 1/4 | 6 mm / 4 mm | 22,5 | 20,0 | 10 mm |
| K- 07 40 33 86 | R 1/4 | 8 mm / 6 mm | 22,5 | 20,0 | 10 mm |
| K- 07 40 33 84 | R 1/4 | 10 mm / 8 mm | 25,5 | 21,5 | 11 mm |
| K- 07 40 33 92 | R 3/8 | 6 mm / 4 mm | 23,5 | 22,5 | 11 mm |
| K- 07 40 33 93 | R 3/8 | 8 mm / 6 mm | 24,0 | 22,5 | 11 mm |
| K- 07 40 33 90 | R 3/8 | 10 mm / 8 mm | 25,5 | 22,5 | 11 mm |
| K- 07 40 33 91 | R 3/8 | 12 mm / 10 mm | 30,0 | 24,5 | 14 mm |