

K-KM MS

Hexagonal lock nuts, brass

Karakteristike

Radni tlak	10 bar
Temperatura medija	max. +90 °C
Okolna temperatura	Max. +90 °C



Napomena

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.
Drugi podatci na zahtjev.

Dodatne informacije

Further types and dimensions on request.

Artikli

Naziv	Navoj	L1 (mm)	SW (veličina ključa)
K- 07 40 34 45	G 1/8	3,5	15 mm
K- 07 40 34 46	G 1/4	3,5	17 mm
K- 07 40 34 47	G 3/8	4,5	19 mm
K- 07 40 34 48	G 1/2	5,0	24 mm
K- 07 40 34 49	G 3/4	5,0	32 mm
K- 07 40 34 50	G 1	6,0	41 mm
K- 07 40 44 33	G 1 1/4	8,5	50 mm
K- 07 40 44 34	G 1 1/2	8,5	60 mm
K- 07 40 44 35	G 2	11,0	70 mm
K- 07 40 34 51	M 10 x 1	4,0	14 mm
K- 07 40 34 52	M 12 x 1	5,0	17 mm
K- 07 40 34 54	M 14 x 1	4,0	19 mm
K- 07 40 34 55	M 16 x 1	5,0	22 mm
K- 07 40 34 56	M 20 x 1,5	4,5	27 mm
K- 07 40 34 57	M 22 x 1	4,5	27 mm
K- 07 40 34 58	M 28 x 1,5	6,0	36 mm