

K-RD NIPPEL KURZ ES

Reducing nipples, short type

HANSA FLEX

Karakteristike

Radni tlak Max. 20 bar

Materijal Oplemenjeni čelik 1.4571



Napomena

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.

Drugi podatci na zahtjev.

Dodatne informacije

Further types and dimensions on request.

Artikli

| Naziv | Vanjski navoj | Unutarnji navoj | L1 (mm) | L2 (mm) | SW (veličina ključa) |
|----------------|---------------|-----------------|------------|------------|----------------------|
| K- 07 40 15 27 | G 1/8 | M 5 | 11,0 | 7,0 | 14 mm |
| K- 07 40 15 26 | G 1/4 | M 5 | 14,0 | 10,0 | 17 mm |
| K- 07 40 15 28 | G 1/4 | G 1/8 | 13,0 | 8,0 | 17 mm |
| K- 07 40 15 33 | G 3/8 | G 1/8 | 13,0 | 9,5 | 19 mm |
| K- 07 40 15 29 | G 3/8 | G 1/4 | 13,0 | 9,5 | 19 mm |
| K- 07 40 15 35 | G 1/2 | G 1/8 | 18,0 | 12,0 | 24 mm |
| K- 07 40 15 34 | G 1/2 | G 1/4 | 15,5 | 11,5 | 22 mm |
| K- 07 40 15 30 | G 1/2 | G 3/8 | 15,5 | 11,5 | 22 mm |
| K- 07 40 15 36 | G 3/4 | G 3/8 | 18,0 | 12,0 | 32 mm |
| K- 07 40 15 31 | G 3/4 | G 1/2 | 21,0 | 14,0 | 32 mm |
| K- 07 40 15 37 | G 1 | G 1/2 | 24,0 | 16,0 | 36 mm |
| K- 07 40 15 32 | G 1 | G 3/4 | 18,0 | 12,0 | 36 mm |