K-KONDENSA DRUKODRAIM PLUS

Drain for compressed air condensate

Karakteristike

Priključna snaga filtra	100 m3/min
Priključna snaga kompresora	10 m3/min
Priključna snaga sušača	20 m3/min



Napomena

Drugi podatci na zahtjev.

Opis

Compact and exceptionally reliable, level-controlled drain for compressed air condensate. The condensate enters the integrated collecting tank, in which the level is continuously monitored. When the condensate reaches the maximum mark, the pilot valve opens and the condensate is forced into the discharge line by the system pressure. The valve closes again when the level reaches the minimum mark. Benefits of »drukodrain plus«: No pressure loss, Diaphragm protected by integrated cup filter, Test button for manual outlet, Auto-reset function, Suitable for all condensate types.

Napomene uz narudžbu

The following voltages on request: 24 VDC, 24 VAC DC, 24 VAC / 50 Hz, 110 VAC / 50 Hz, 115 V / 50 Hz

Artikl

Naziv	Radni tlak bari	Napon
K- 07 25 09 24	0.2 - 16 bar	230 VAC / 50 Hz

Usprkos pažljivoj provjeri ne mogu se isključiti pogreške i zbog toga ne preuzimamo odgovornost za sadržane podatke.