


Karakteristike			
Ulazni tlak	Max. 15 bar		
Priključak	G 1/4 internal / external		
Materijal	Mjed		





## Napomena

Dependent on the input pressure P1, the initial pressure P2 can vary between -20% to +20% Drugi podatci na zahtjev.

## **Opis**

Industry, trade and repair shops often require working pressures of 15 bar or less. These pressure reducing valves, which are screwed directly onto the tool, enable the actually necessary working pressure to be set. <br/> Senefits: Significantly reduced risk of accidents, Longer tool life with fewer malfunctions, Lower noise levels at the workplace.

Artikl								
Naziv	Tlak namještanja	maks. protok (L/min)	A (mm)	В	Ø C (mm)	SW (mm)		
K- 07 25 19 31	2,0	300	34,0	9,0 mm	17,0	17		
K- 07 25 02 00	3,0	360	34,0	9,0 mm	17,0	17		
K- 07 25 02 01	4,0	380	34,0	9,0 mm	17,0	17		
K- 07 25 02 02	5,0	390	34,0	9,0 mm	17,0	17		
K- 07 25 02 03	6,0	405	34,0	9,0 mm	17,0	17		
K- 07 25 19 32	7,0	415	34,0	9,0 mm	17,0	17		
K- 07 25 19 33	8,0	420	34,0	9,0 mm	17,0	17		