

K-FLASCHENDRUCKR 300 N GASE

Regulator tlaka za plinsku bocu, tlak boce 300 bar, za nezapaljive plinove

HANSA FLEX

Karakteristike

Manometar sadržaja	0 - 200/315 bar (max. cylinder pressure 200 bar), 0 - 300/400 bar (max. cylinder pressure 300 bar), 0 - 18/40 bar for acetylene
Materijal	Prešana mjed
Priključak za bocu	W 30 x 2



Napomena

Drugi podatci na zahtjev.

Opis

Single-stage type of construction acc. to DIN EN ISO 2503, with shut-off valve and safety valve as well as pressure gauges for the cylinder contents and working pressure.

Artikli

Naziv	Vrsta plina	Radni tlak bari
K- 07 25 07 22	Oxygen	0 - 10,0 bar
K- 07 25 07 23	Compressed air	0 - 10,0 bar
K- 07 25 07 24	Nitrogen	0 - 10,0 bar
K- 07 25 07 25	Nitrogen	0 - 20,0 bar

Rezervni dijelovi

K-MANO SCHWEISSTECHNIK	Content pressure gauge
K-MANO SCHW	Pressure gauges for welding
K-SCHUTZKAPPE MANOMETER	Zaštitne kapice