

# K-3/2-BKR HANSA

## Ball valves

**HANSA FLEX**

### Karakteristike

|                              |   |
|------------------------------|---|
| Ulazni tlak                  | 0 - 16 bar                                      |
| Temperaturno područje        | -10 °C to +50 °C                                |
| Mediji                       | komprimirani zrak                               |
| Navoj priključka             | Material: Die-cast zinc                         |
| Kućište                      | Material: Grivory® (PA 66)                      |
| Mjerenje vrijednosti protoka | At P2 = 6 bar, pressure drop $\Delta p = 1$ bar |



### Napomena

Drugi podatci na zahtjev.

### Opis

Closable ball valve in 3/2-way design, mechanically actuated. Toggle 90° rotatable and with switch position indicator: Traverse: Inlet port blocked - outlet port exhausted

Longitudinal: Inlet port and outlet port connected - exhaust blocked. Exhaust air can be collected.

### Dodatne informacije

The price does not include a padlock. Please order separately.

### Artikli

| Naziv          | Navoj | Odvojak | Protok (L/min) | A (mm) | B        | C (mm) |
|----------------|-------|---------|----------------|--------|----------|--------|
| K- 07 25 11 23 | G 1/4 | 1/4     | 1900           | 52,0   | 87,5 mm  | 54,5   |
| K- 07 25 11 24 | G 3/8 | 1/4     | 1900           | 52,0   | 87,5 mm  | 54,5   |
| K- 07 25 11 43 | G 3/8 | 1/2     | 11000          | 63,0   | 127,0 mm | 70,5   |
| K- 07 25 11 44 | G 1/2 | 1/2     | 11000          | 63,0   | 127,0 mm | 70,5   |
| K- 07 25 11 45 | G 3/4 | 3/4     | 25000          | 85,0   | 144,7 mm | 93,7   |
| K- 07 25 11 46 | G 1   | 3/4     | 25000          | 85,0   | 144,7 mm | 93,7   |

### Pribor

K-VORHAENGESCHLOSS Padlock

### Rezervni dijelovi

K-HALTERBAUSATZ HANSA Holder HANSA