

K-3/2-BKR MULTIFIX

Ball valves

HANSA FLEX

Karakteristike

| | |
|------------------------------|---|
| Ulazni tlak | Max. 16 bar |
| Temperatura medija | max. 60 °C |
| Okolna temperatura | Max. 60 °C |
| Aktiviranje | Twist knob, rotatable 90° |
| Odzračni priključak | Silencer G 1/4 (K-07251158, K-07251159), G 1/2 (K-07251160, K-07251161, K-07251950) |
| Brtveni materijal | NBR |
| Kućište | Die-cast zinc, Aluminium for G 1 variant |
| Mjerenje vrijednosti protoka | At P1 = 6 bar and pressure drop $\Delta p = 1$ bar |



Napomena

Drugi podatci na zahtjev.

Opis

Rotary switch can be turned 90°, lockable, with relief port

Artikli

| Naziv | Navoj | Protok (L/min) | A (mm) | B | C (mm) | D (mm) | Veličina |
|----------------|-------|----------------|--------|----------|--------|--------|----------|
| K- 07 25 11 58 | G 1/4 | 2800 | 47,8 | 81,4 mm | 55,4 | 26,0 | 1 |
| K- 07 25 11 59 | G 3/8 | 2800 | 47,8 | 81,4 mm | 55,4 | 26,0 | 1 |
| K- 07 25 11 60 | G 1/2 | 11000 | 68,8 | 102,6 mm | 69,1 | 33,5 | 2 |
| K- 07 25 11 61 | G 3/4 | 11000 | 68,8 | 102,6 mm | 69,1 | 33,5 | 2 |
| K- 07 25 19 50 | G 1 | 25000 | 82,8 | 133,5 mm | 83,0 | 50,5 | 3 |

Pribor

K-SCHALLDAE SINTERBR GE MS1 Silencers, sintered bronze, with brass hexagon nut and brass thread

Rezervni dijelovi

| | |
|--------------------------|-----------------|
| K-KOPPELPAKET MEHR | Coupling packet |
| K-KOPPELPAKET SCHMA | Coupling packet |
| K-HALTERBAUSATZ MULTIFIX | Holder |