


K-FI PC-BEHAEL H ABLV MULTIFX MINI

Filters with polycarbonate bowl and semi-automatic drain valve

HANSA FLEX

Karakteristike

| | |
|---------------------------------------|--|
| Ulazni tlak | Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl) |
| Temperatura medija | max. 60 °C |
| Okolna temperatura | Max. 60 °C |
| Protok | 1000 l/min |
| Veličina pora u filterarskom elementu | 5 µm |
| Kućište | Die-cast zinc |
| Drain valve | Semi-automatic |
| Mjerenje vrijednosti protoka | At P2 = 6 bar and pressure drop $\Delta p = 1$ bar |



Napomena

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar.
Drugi podatci na zahtjev.

Opis

Centrifugal separators with a sintered filter element.

Artikli

| Naziv | Navoj | A (mm) | B | C (mm) | D (mm) | DN | Veličina |
|----------------|-------|--------|----------|--------|--------|----|----------|
| K- 07 25 00 42 | G 1/8 | 40,0 | 114,8 mm | 12,3 | 102,5 | 5 | 0 |
| K- 07 25 00 44 | G 1/4 | 40,0 | 114,8 mm | 12,3 | 102,5 | 5 | 0 |

Rezervni dijelovi

| | |
|--------------------------------|--|
| K-AUTOMAT ABLASSVENTIL | Automatic drain valve |
| K-KOPPELPAKET MEHR | Coupling packet |
| K-ERSATZBEHAELTER MULTI MINI | Spare tank »multifix-mini« & »standard-mini« |
| K-PC-BEHAELTER FILTER MULTIFIX | Polycarbonate tank filter |
| K-FILTERELEMENT | Filter element |