

K-SCHALTVENTILE 3/2 MULTIFIX MINI

On-off valves (3/2-way valves)

HANSA FLEX

Karakteristike

| | |
|--------------------------------|--|
| Ulazni tlak | Min. 2 bar, max. 10 bar |
| Temperatura medija | max. 60 °C |
| Okolna temperatura | Max. 60 °C |
| Električni priključak | Device plug PG 9, type B, EN 175301-803 |
| Vrsta zaštite | IP 65 (P 54) acc. to DIN 40050 |
| Protok | 1600 l/min |
| Trajanje uključanja, relativno | 100 % |
| Odzračni priključak | Silencer G 1/4 |
| Brtveni materijal | NBR |
| Kućište | Die-cast zinc |
| Mjerenje vrijednosti protoka | At P1 = 6 bar and pressure drop $\Delta p = 1$ bar |



Napomena

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar.

Drugi podatci na zahtjev.

Opis

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal. When they are switched off, the system is relieved at the same time.

Artikli

| Naziv | Navoj | Magnetni svitak | A (mm) | B | C (mm) | Veličina |
|----------------|-------|-----------------|-----------|---------|-----------|----------|
| K- 07 25 11 62 | G 1/4 | 230 V AC, 50 Hz | 45,0 | 29,0 mm | 96,0 | 0 |
| K- 07 25 11 63 | G 1/4 | 110 V AC, 50 Hz | 45,0 | 29,0 mm | 96,0 | 0 |
| K- 07 25 11 64 | G 1/4 | 24 V DC | 45,0 | 29,0 mm | 96,0 | 0 |

Rezervni dijelovi

| | |
|------------------------------|-------------------------------------|
| K-KOPPELPAKET MEHR | Coupling packet |
| K-GERAETESTECKER | Coupling socket |
| K-AUTOMAT ABLASSVENTIL | Automatic drain valve |
| K-MAGNETSPULE MULTIFIX | Solenoid |
| K-SCHALLDAE SINTERBR SCHLITZ | Silencers, sintered bronze, slotted |