

# K-SCHALTVENTILE 3/2 MULTIFIX MINI

On-off valves (3/2-way valves)

**HANSA FLEX**

## Karakteristike

Ulazni tlak	Min. 2 bar, max. 10 bar
Temperatura medija	max. 60 °C
Okolna temperatura	Max. 60 °C
Električni priključak	Device plug PG 9, type B, EN 175301-803
Vrsta zaštite	IP 65 (P 54) acc. to DIN 40050
Protok	1600 l/min
Trajanje uključanja, relativno	100 %
Odzračni priključak	Silencer G 1/4
Brtnveni materijal	NBR
Kućište	Die-cast zinc
Mjerenje vrijednosti protoka	At P1 = 6 bar and pressure drop $\Delta p = 1$ bar



## Napomena

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar.

Drugi podatci na zahtjev.

## Opis

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal. When they are switched off, the system is relieved at the same time.

## Artikli

Naziv	Navoj	Magnetni svitak	A (mm)	B	C (mm)	Veličina
K- 07 25 11 62	G 1/4	230 V AC, 50 Hz	45,0	29,0 mm	96,0	0
K- 07 25 11 63	G 1/4	110 V AC, 50 Hz	45,0	29,0 mm	96,0	0
K- 07 25 11 64	G 1/4	24 V DC	45,0	29,0 mm	96,0	0

## Rezervni dijelovi

K-KOPPELPAKET MEHR	Coupling packet
K-GERAETESTECKER	Coupling socket
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-MAGNETSPULE MULTIFIX	Solenoid
K-SCHALLDAE SINTERBR SCHLITZ	Silencers, sintered bronze, slotted