

K-WTEH 2-TLG MET TROPF MULTIFIX MIN

Service units, 2-piece with metal bowl and metal sight dome

HANSA FLEX

Karakteristike

| | |
|--------------------------------------|----------------------------------------------------------------|
| Ulazni tlak | Max. 12 bar (also for metal tank!) |
| Temperatura medija | max. 60 °C |
| Okolna temperatura | Max. 60 °C |
| Veličina pora u filteraskom elementu | 5 µm |
| Brtnveni materijal | NBR |
| Pokrov s oprugom | POM-brass |
| Kučičšte | Die-cast zinc |
| Nastavak za kapanje | PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl) |
| Drain valve | Semi-automatic |
| Mjerenje vrijednosti protoka | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |



Napomena

Drugi podatci na zahtjev.

Opis

Two or three-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Napomene uz narudžbu

Lockable service units available on request. If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar.

Artikli

| Naziv | Navoj | Regulacijsko područje | Protok (L/min) | A (mm) | B | C (mm) | D (mm) | DN | Veličina |
|----------------|-------|-----------------------|----------------|--------|----------|--------|--------|----|----------|
| K- 07 25 01 26 | G 1/8 | 0.5 - 10 bar | 700 | 80,0 | 162,0 mm | 63,0 | 99,0 | 5 | 0 |
| K- 07 25 01 28 | G 1/4 | 0.5 - 10 bar | 700 | 80,0 | 162,0 mm | 63,0 | 99,0 | 5 | 0 |

Rezervni dijelovi

| | |
|--------------------------------|----------------------------------------------|
| K-HALTERBAUSATZ | Holder |
| K-AUTOMAT ABLASSVENTIL | Automatic drain valve |
| K-SCHALTTAFELMUTTER | Nut |
| K-KOPPELPAKET MEHR | Coupling packet |
| K-PC-BEHAELTER FILTER MULTIFIX | Polycarbonate tank filter |
| K-ERSATZBEHAELTER MULTI MINI | Spare tank »multifix-mini« & »standard-mini« |
| K-FILTERELEMENT | Filter element |
| K-VERSCHLEI-SATZ | Set of wearing parts |
| K-TROPFAUFSATZ POLYCARBO 1 | Drip attachment polycarbonate |
| K-TROPFAUFSATZ METALL | Drip attachment metal |