

K-KONSTANT DRUCKREGLER STANDARD 1

Constant-pressure regulators

HANSA FLEX

Karakteristike

| | |
|------------------------------|--|
| Ulazni tlak | Max. 25 bar (G 1/4 to G 1/2), Max. 40 bar (G 3/4 to G 1 1/2) |
| Temperatura medija | max. 60 °C |
| Okolna temperatura | Max. 90 °C |
| Brtveni materijal | NBR |
| Kućište | Die-cast zinc for (G 1/4 to G 1/2), for Brass (G 3/4 to G 1 1/2) |
| Mjerenje vrijednosti protoka | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |
| Drugi podatci | User manual on request |



Opis

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design. The pressure regulators maintain a constant working pressure regardless of variations in the inlet pressure.

Artikli

| Naziv | Navoj | Regulacijsko područje | Protok (L/min) | A (mm) | B | C (mm) | D (mm) | DN |
|----------------|-------|-----------------------|----------------|--------|----------|--------|--------|----|
| K- 07 25 03 82 | G 1/4 | 0.5 - 3 bar | 3000 | 77,0 | 165,0 mm | 33,0 | 132,0 | 10 |
| K- 07 25 03 83 | G 1/4 | 0.5 - 6 bar | 2500 | 77,0 | 165,0 mm | 33,0 | 132,0 | 10 |
| K- 07 25 03 84 | G 1/4 | 0.5 - 10 bar | 2000 | 77,0 | 165,0 mm | 33,0 | 132,0 | 10 |
| K- 07 25 03 85 | G 1/4 | 0.5 - 16 bar | 1600 | 77,0 | 165,0 mm | 33,0 | 132,0 | 10 |
| K- 07 25 03 86 | G 3/8 | 0.5 - 3 bar | 3000 | 70,0 | 165,0 mm | 33,0 | 132,0 | 10 |
| K- 07 25 03 87 | G 3/8 | 0.5 - 6 bar | 2500 | 70,0 | 165,0 mm | 33,0 | 132,0 | 10 |
| K- 07 25 03 88 | G 3/8 | 0.5 - 10 bar | 2000 | 70,0 | 165,0 mm | 33,0 | 132,0 | 10 |
| K- 07 25 03 89 | G 3/8 | 0.5 - 16 bar | 1600 | 70,0 | 165,0 mm | 33,0 | 132,0 | 10 |
| K- 07 25 03 90 | G 3/8 | 0.5 - 3 bar | 3500 | 90,0 | 170,0 mm | 32,0 | 138,0 | 15 |
| K- 07 25 03 91 | G 3/8 | 0.5 - 6 bar | 3000 | 90,0 | 170,0 mm | 32,0 | 138,0 | 15 |
| K- 07 25 03 92 | G 3/8 | 0.5 - 10 bar | 2670 | 90,0 | 170,0 mm | 32,0 | 138,0 | 15 |
| K- 07 25 03 93 | G 3/8 | 0.5 - 16 bar | 2000 | 90,0 | 170,0 mm | 32,0 | 138,0 | 15 |
| K- 07 25 03 94 | G 1/2 | 0.5 - 3 bar | 3500 | 82,0 | 170,0 mm | 32,0 | 138,0 | 15 |
| K- 07 25 03 95 | G 1/2 | 0.5 - 6 bar | 3000 | 82,0 | 170,0 mm | 32,0 | 138,0 | 15 |
| K- 07 25 03 96 | G 1/2 | 0.5 - 10 bar | 2670 | 82,0 | 170,0 mm | 32,0 | 138,0 | 15 |
| K- 07 25 03 97 | G 1/2 | 0.5 - 16 bar | 2000 | 82,0 | 170,0 mm | 32,0 | 138,0 | 15 |

Rezervni dijelovi

| | |
|--------------------------|--------------------------------------|
| K-HALTERBAUSATZ STANDARD | Holder |
| K-VERSCHLEI-SATZ | Set of wearing parts |
| K-RD NIPPEL KURZ 1 | Reducing nipples, short type |
| K-XV AGM 2 | Double nipples, parallel male thread |