

# K-WMV 3/2 MANU DREHKNOPF

3/2-way miniature valves, manually operated, with rotary knob (2 positions)

**HANSA FLEX**

## Karakteristike

|                        |                     |
|------------------------|---------------------|
| Funkcija               | NC                  |
| Radni tlak             | 0,5 - 10 bar        |
| Radna temperatura      | od -10 °C do +60 °C |
| Protok 6bar i 5bar     | 35 NI/min           |
| Nazivni Ø              | 2,5 mm              |
| Tlak aktiviranja 6 bar | 8 N                 |
| Tijelo ventila         | aluminij            |
| Pritisna tipka         | ponikladni mjed     |
| Opruga                 | nehrđajući čelik    |
| Brtvni materijal       | NBR                 |



## Napomena

Drugi podatci na zahtjev.

## Opis

Monostable (non-latching) and bistable (latching) versions available.

## Artikli

| Naziv          | Priključak | Aktiviranje |
|----------------|------------|-------------|
| K- 07 15 00 54 | 4 mm bočno | monostable  |
| K- 07 15 00 55 | M 5 bočno  | monostable  |
| K- 07 15 00 56 | 4 mm bočno | bistabilno  |
| K- 07 15 00 57 | M 5 bočno  | bistabilno  |