

# K-DV STECK B SCHLITZ

Bidirectional flow control valves, air restriction at both ends (»B«), plug-in connector

**HANSA FLEX**

## Karakteristike

|   |                                    |
|---|------------------------------------|
| Radni tlak  | maks. 10 bar                       |
| Temperaturno područje                             | 0 °C to +70 °C                     |
| Šuplji vijak, zakretni krak, vijak za reguliranje | Nickel-plated brass                |
| Unutarnji dijelovi                                | Brass with a bare metal surface    |
| Brtvena usna O-prsten                             | NBR                                |
| Brtve (sa zaštitom od ispadanja)                  | Polyamide (glass fibre-reinforced) |



## Napomena

Drugi podatci na zahtjev.

## Opis

For regulation of a cylinder piston speed at both ends and control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly. Compact type of construction, also ideal where space is restricted.

## Artikli

| Naziv          | C (mm) | za crijevo | Navoj | SW (veličina ključa) | B (mm) |
|----------------|--------|------------|-------|----------------------|--------|
| K- 07 15 05 01 | 18,6   | 4 mm       | M 5   | 8 mm                 | 24,5   |
| K- 07 15 05 02 | 21,7   | 6 mm       | M 5   | 8 mm                 | 24,5   |
| K- 07 15 05 06 | 20,6   | 4 mm       | G 1/8 | 14 mm                | 32,0   |
| K- 07 15 05 07 | 22,7   | 6 mm       | G 1/8 | 14 mm                | 32,0   |
| K- 07 15 05 08 | 23,7   | 8 mm       | G 1/8 | 14 mm                | 32,0   |
| K- 07 15 05 04 | 24,2   | 6 mm       | G 1/4 | 17 mm                | 40,0   |
| K- 07 15 05 05 | 24,7   | 8 mm       | G 1/4 | 17 mm                | 40,0   |
| K- 07 15 05 03 | 26,8   | 10 mm      | G 1/4 | 17 mm                | 40,0   |
| K- 07 15 05 09 | 28,8   | 10 mm      | G 3/8 | 20 mm                | 50,0   |