

K-HS RD

Unidirectional banjo valves, pneumatic release, port 2 with female thread

HANSA FLEX

Karakteristike

| | |
|--------------------|----------------------------------------------------------------------|
| Radni tlak | 0.3 - 10 bar |
| Upravljački tlak | 0.5 - 2.5 bar, depending on operating pressure |
| Temperatura medija | max. 60 °C |
| Ugradbeni položaj | Any. The ring piece must be positioned before the valve is tightened |
| Materijal | poniklani mjed |
| Brtnveni materijal | Perbunan |



Napomena

Drugi podatci na zahtjev.

Opis

For stopping and positioning the cylinder movement: If a control signal is present at port 3 (see drawing), air can flow to and from the cylinder. If no control signal is present, the cylinder exhaust air is shut off by the unidirectional valve. The cylinder is stopped. Releasable unidirectional valves are screwed directly onto the cylinder instead of the normal pipe connections.

Artikli

| Naziv | Port 1 | Port 2 | Priključak 3 | B (mm) | C (mm) |
|----------------|--------|--------|--------------|-----------|-----------|
| K- 07 15 07 04 | G 1/8 | G 1/8 | M 5 | 38,0 | 21,5 |
| K- 07 15 07 03 | G 1/4 | G 1/4 | G 1/8 | 43,0 | 25,4 |
| K- 07 15 07 05 | G 3/8 | G 3/8 | G 1/8 | 46,0 | 31,6 |
| K- 07 15 07 02 | G 1/2 | G 1/2 | G 1/8 | 52,0 | 32,0 |