

K-MAGV MINI

Miniature solenoid valves 15 mm

HANSA FLEX

Karakteristike

Mediji	Filtered, unlubricated compressed air
Područje tlaka	0 - 7 bar (NC) with silver plate at manual override 0 - 5 bar (NO) with black plate at manual override
Priključak	In manifold base
Temperaturno područje	-5 °C to +45 °C
Vrijeme otvaranja / vrijeme zatvaranja	10 - 12 ms (depending on pressure)
Snaga svitka	2,5 W
Materijal	Plastika
Brtveni materijal	NBR, stainless steel



Napomena

Drugi podatci na zahtjev.

Opis

Directly controlled 3/2-way solenoid valves specially designed for pneumatic applications. These valves are provided with a flange for assembly on an individual base or multiple manifold base. They feature a monostable manual operator. The scope of supply includes two fixing bolts and a flange gasket. The coils can be turned 180°.

Dodatne informacije

Important: The scope of supply does not include a connector. Please order separately.

Artikli

Naziv	Funkcija	Napon	Priključak	H (mm)	B (mm)
K- 07 15 14 18	NC	24 V DC	Cable (30 cm)	42,0	15,0
K- 07 15 14 19	NC	24 V DC	for system plug	42,0	15,0
K- 07 15 14 20	NC	12 V DC	Cable (30 cm)	42,0	15,0
K- 07 15 14 21	NC	12 V DC	for system plug	42,0	15,0
K- 07 15 14 22	NO	24 V DC	Cable (30 cm)	42,0	15,0
K- 07 15 14 23	NO	24 V DC	for system plug	42,0	15,0
K- 07 15 14 24	NO	12 V DC	Cable (30 cm)	42,0	15,0
K- 07 15 14 25	NO	12 V DC	for system plug	42,0	15,0