

K-WV 3/2 ELEKTROPNEUMATISCH

3/2-way pilot valves

HANSA FLEX

Karakteristike

Radni tlak	2,5 - 10 bar (monostable)\n1,0 - 10 bar (bistable)\ninvacuum up to 10 bar (external pilot air)
min. radni tlak	2.5 bar (monostable), 1.0 bar (bistable)
Temperaturno področje	-10 °C to +60 °C
Protok 6bar i 10bar	550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2)
Protok 6bar i 5bar	400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2)



Napomena

Drugi podatki na zahtjev.

Artikli

Naziv	Priključak	Napon	DN	Funkcija	Br. spojne sheme	Upravljanje
K- 07 15 00 23	G 1/8	24 V DC	5	3/-way NO	32	
K- 07 15 00 24	G 1/4	24 V DC	8	3/-way NO	32	
K- 07 15 25 75	G 3/8	24 V DC	13	3/-way NO	32	
K- 07 15 00 25	G 1/2"	24 V DC	15	3/-way NO	32	
K- 07 15 00 26	G 1/8	230 V, 50 Hz	5	3/-way NO	32	
K- 07 15 00 27	G 1/4	230 V, 50 Hz	8	3/-way NO	32	
K- 07 15 25 76	G 3/8	230 V, 50 Hz	13	3/-way NO	32	
K- 07 15 00 28	G 1/2"	230 V, 50 Hz	15	3/-way NO	32	
K- 07 15 00 29	G 1/8	24 V DC	5	3/2-way NC	33	
K- 07 15 00 30	G 1/4	24 V DC	8	3/2-way NC	33	
K- 07 15 25 77	G 3/8	24 V DC	13	3/2-way NC	33	
K- 07 15 00 31	G 1/2"	24 V DC	15	3/2-way NC	33	
K- 07 15 00 32	G 1/8	230 V, 50 Hz	5	3/2-way NC	33	
K- 07 15 00 33	G 1/4	230 V, 50 Hz	8	3/2-way NC	33	
K- 07 15 25 78	G 3/8	230 V, 50 Hz	13	3/2-way NC	33	
K- 07 15 00 34	G 1/2"	230 V, 50 Hz	15	3/2-way NC	33	
K- 07 15 00 35	G 1/8	24 V DC	5	3/2-way	34	
K- 07 15 00 36	G 1/4	24 V DC	8	3/2-way	34	
K- 07 15 25 79	G 3/8	24 V DC	13	3/2-way	34	
K- 07 15 00 37	G 1/2"	24 V DC	15	3/2-way	34	
K- 07 15 00 38	G 1/8	230 V, 50 Hz	5	3/2-way	34	
K- 07 15 00 39	G 1/4	230 V, 50 Hz	8	3/2-way	34	
K- 07 15 25 80	G 3/8	230 V, 50 Hz	13	3/2-way	34	
K- 07 15 00 40	G 1/2"	230 V, 50 Hz	15	3/2-way	34	