

# K-WV 5/3 ELEKTROPNEU MITTELSTELLUNG

5/3-way pilot valves (monostable)

**HANSA FLEX**

## Karakteristike

|                       |                                                                                                |
|-----------------------|------------------------------------------------------------------------------------------------|
| Radni tlak            | 2,5 - 10 bar (monostable)\n1,0 - 10 bar (bistable)\ninvacuum up to 10 bar (external pilot air) |
| min. radni tlak       | 2.5 bar (monostable), 1.0 bar (bistable)                                                       |
| Temperaturno područje | -10 °C to +60 °C                                                                               |
| Protok 6bar i 10bar   | 550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2)              |
| Protok 6bar i 5bar    | 400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2)               |



## Napomena

Drugi podatci na zahtjev.

## Artikli

| Naziv          | Priključak | Napon        | DN | Funkcija | Br. spojne sheme |
|----------------|------------|--------------|----|----------|------------------|
| K- 07 15 03 30 | G 1/8      | 24 V DC      | 5  | 5/3-way  | 37               |
| K- 07 15 03 31 | G 1/4      | 24 V DC      | 8  | 5/3-way  | 37               |
| K- 07 15 25 87 | G 3/8      | 24 V DC      | 13 | 5/3-way  | 37               |
| K- 07 15 03 32 | G 1/2"     | 24 V DC      | 15 | 5/3-way  | 37               |
| K- 07 15 03 33 | G 1/8      | 230 V, 50 Hz | 5  | 5/3-way  | 37               |
| K- 07 15 03 34 | G 1/4      | 230 V, 50 Hz | 8  | 5/3-way  | 37               |
| K- 07 15 25 88 | G 3/8      | 230 V, 50 Hz | 13 | 5/3-way  | 37               |
| K- 07 15 03 35 | G 1/2"     | 230 V, 50 Hz | 15 | 5/3-way  | 37               |
| K- 07 15 03 36 | G 1/8      | 24 V DC      | 5  | 5/3-way  | 38               |
| K- 07 15 03 37 | G 1/4      | 24 V DC      | 8  | 5/3-way  | 38               |
| K- 07 15 25 89 | G 3/8      | 24 V DC      | 13 | 5/3-way  | 38               |
| K- 07 15 03 38 | G 1/2"     | 24 V DC      | 15 | 5/3-way  | 38               |
| K- 07 15 03 39 | G 1/8      | 230 V, 50 Hz | 5  | 5/3-way  | 38               |
| K- 07 15 03 40 | G 1/4      | 230 V, 50 Hz | 8  | 5/3-way  | 38               |
| K- 07 15 25 90 | G 3/8      | 230 V, 50 Hz | 13 | 5/3-way  | 38               |
| K- 07 15 03 41 | G 1/2"     | 230 V, 50 Hz | 15 | 5/3-way  | 38               |
| K- 07 15 03 42 | G 1/8      | 24 V DC      | 5  | 5/3-way  | 39               |
| K- 07 15 25 91 | G 3/8      | 24 V DC      | 13 | 5/3-way  | 39               |
| K- 07 15 03 43 | G 1/4      | 24 V DC      | 8  | 5/3-way  | 39               |
| K- 07 15 03 44 | G 1/2"     | 24 V DC      | 15 | 5/3-way  | 39               |
| K- 07 15 03 45 | G 1/8      | 230 V, 50 Hz | 5  | 5/3-way  | 39               |
| K- 07 15 03 46 | G 1/4      | 230 V, 50 Hz | 8  | 5/3-way  | 39               |
| K- 07 15 25 92 | G 3/8      | 230 V, 50 Hz | 13 | 5/3-way  | 39               |
| K- 07 15 03 47 | G 1/2"     | 230 V, 50 Hz | 15 | 5/3-way  | 39               |