# K-WV 3/2 MANU DRUCKKNOPF

3/2-way pilot valve, manually operated, with pushbutton, NC

## Karakteristike

| | |
|---|---|
| **Radni tlak** | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| **Temperaturno područje** | -10 °C to +60 °C |
| **Protok 6bar i 10bar** | 550 Nl/min |
| **Protok 6bar i 5bar** | 400 Nl/min |
| **Aktiviranje** | Monostable |
| **Tijelo ventila** | aluminij |
| **Opruga** | Special steel |
| **Klip** | Aluminium |
| **Brtveni materijal** | NBR |



## Napomena

3 valve positions only in conjunction with a second 3/2-way valve. <br>Corresponds to a 5/3-way valve.
Drugi podatci na zahtjev.

## Dodatne informacije

Important: The scope of supply does not include a connector. Please order separately.

## Artikl

| Naziv | Priključak | Simbol | Aktiviranje | Pločica |
|---|---|---|---|---|
| **K- 07 15 00 76** | G 1/8 | 4 | monostable | Red/black |

*Usprkos pažljivoj provjeri ne mogu se isključiti pogreške i zbog toga ne preuzimamo odgovornost za sadržane podatke.*