


# K-WV 5/2 PNEUMATISCH

5/2-way pilot valves

**HANSA FLEX**

## Karakteristike

Radni tlak	Max. vacuum 10 bar
min. radni tlak	2.5 bar (monostable), 1.0 bar (bistable)
Temperaturno področje	-10 °C to +60 °C
Protok 6bar i 10bar	550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2)
Protok 6bar i 5bar	400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2)
Priključak za upravljački zrak	G 1/8



## Napomena

Drugi podatki na zahtjev.

## Artikli

Naziv	Priključak	DN	Funkcija	Br. spojne sheme	Upravljanje
K- 07 15 02 11	G 1/8	5	5/2-way	27	
K- 07 15 02 12	G 1/4	8	5/2-way	27	
K- 07 15 25 70	G 3/8	13	5/2-way	27	
K- 07 15 02 15	G 1/2"	15	5/2-way	27	
K- 07 15 02 13	G 1/8	5	5/2-way	28	
K- 07 15 02 14	G 1/4	8	5/2-way	28	
K- 07 15 25 71	G 3/8	13	5/2-way	28	
K- 07 15 02 16	G 1/2"	15	5/2-way	28	