


K-WV 5/3 MITTELSTELLUNSVENT

5/3-way pilot valves (monostable)

HANSA FLEX

Karakteristike

| | |
|-----------------------|---|
| Funkcija | 5/3-way |
| Radni tlak | Max. vacuum 10 bar |
| min. radni tlak | |
| Temperaturno područje | -10 °C to +60 °C |
| Protok 6bar i 10bar | 550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2) |
| Protok 6bar i 5bar | 400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2) |



Napomena

Drugi podatci na zahtjev.

Artikli

| Naziv | Priključak | DN | Funkcija | Br. spojne sheme |
|----------------|------------|----|----------|------------------|
| K- 07 15 03 48 | G 1/8 | 5 | 5/3-way | 29 |
| K- 07 15 03 49 | G 1/8 | 5 | 5/3-way | 30 |
| K- 07 15 03 50 | G 1/8 | 5 | 5/3-way | 31 |
| K- 07 15 03 51 | G 1/4 | 8 | 5/3-way | 29 |
| K- 07 15 03 52 | G 1/4 | 8 | 5/3-way | 30 |
| K- 07 15 03 53 | G 1/4 | 8 | 5/3-way | 31 |
| K- 07 15 25 72 | G 3/8 | 13 | 5/3-way | 29 |
| K- 07 15 25 73 | G 3/8 | 13 | 5/3-way | 30 |
| K- 07 15 25 74 | G 3/8 | 13 | 5/3-way | 31 |
| K- 07 15 03 54 | G 1/2" | 15 | 5/3-way | 29 |
| K- 07 15 03 55 | G 1/2" | 15 | 5/3-way | 30 |
| K- 07 15 03 56 | G 1/2" | 15 | 5/3-way | 31 |