

# K-WV 5/3 MITTELSTELLUNSVENT

5/3-way pilot valves (monostable)

**HANSA FLEX**

## Karakteristike

|                       |   |
|-----------------------|---|
| Funkcija              | 5/3-way   |
| Radni tlak            | Max. vacuum 10 bar  |
| min. radni tlak       |   |
| Temperaturno područje | -10 °C to +60 °C  |
| Protok 6bar i 10bar   | 550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2) |
| Protok 6bar i 5bar    | 400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2)  |



## Napomena

Drugi podatci na zahtjev.

## Artikli

| Naziv          | Priključak | DN | Funkcija | Br. spojne sheme |
|----------------|------------|----|----------|------------------|
| K- 07 15 03 48 | G 1/8      | 5  | 5/3-way  | 29               |
| K- 07 15 03 49 | G 1/8      | 5  | 5/3-way  | 30               |
| K- 07 15 03 50 | G 1/8      | 5  | 5/3-way  | 31               |
| K- 07 15 03 51 | G 1/4      | 8  | 5/3-way  | 29               |
| K- 07 15 03 52 | G 1/4      | 8  | 5/3-way  | 30               |
| K- 07 15 03 53 | G 1/4      | 8  | 5/3-way  | 31               |
| K- 07 15 25 72 | G 3/8      | 13 | 5/3-way  | 29               |
| K- 07 15 25 73 | G 3/8      | 13 | 5/3-way  | 30               |
| K- 07 15 25 74 | G 3/8      | 13 | 5/3-way  | 31               |
| K- 07 15 03 54 | G 1/2"     | 15 | 5/3-way  | 29               |
| K- 07 15 03 55 | G 1/2"     | 15 | 5/3-way  | 30               |
| K- 07 15 03 56 | G 1/2"     | 15 | 5/3-way  | 31               |