

K-VT 2 KUPPL 7,2 STECKNIP MS

Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8

HANSA FLEX

Karakteristike

Radni tlak	0 - 35 bar
Temperatura medija	-20 °C to +100 °C
Kućište	Brass
Osigurač i brtva	Industrial glue, mid hardened



Napomena

Couplings and distributors are also available separately
Drugi podatci na zahtjev.

Opis

1, 2 or 3-way distributor pieces made of brass, pre-assembled with quick disconnect coupling DN 7.2. Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

Dodatne informacije

Couplings and distributors are also available separately

Artiki

Naziv	Priključak	Spojka	Sastoji se od razvodnika
K- 07 40 40 48	Plugs DN 7.2 to 7.8 / G 3/8	K-07350025	K-07404016
K- 07 40 44 27	Plugs DN 7.2 to 7.8 / G 1/2	K-07350026	K-07404017

je pribor uz sljedeće proizvode

K-VSEH 3-KRAFT	Receptacle combinations »3-Kraft«
K-VSEH AIRKRAFT	Receptacle combinations »airkraft«