

# K-RUNDDUESE LAERMARME

Low-noise round nozzles

**HANSA FLEX**



## Napomena

For noise, air consumption and blowing force values, see diagrams 1-17 in the technical information.

## Opis

If correctly designed, these noise-reducing nozzles guarantee a lower noise level than conventional one-hole types with an identical blowing force. They are usually fitted with a noise-reducing plastic insert and they are recommended by the German BGIA (Institute for Occupational Safety and Health).

## Artikl

| Naziv          | Navoj      | Duljina<br>(mm) | Ø sapnice izvana<br>(mm) | Materijal           | Dijagram |
|----------------|------------|-----------------|--------------------------|---------------------|----------|
| K- 07 10 09 56 | G 3/8 male | 55,0            | 11                       | Nickel-plated brass | 3        |
| K- 07 10 09 57 | G 3/8 male | 50,0            | 10                       | Aluminij            | 4        |
| K- 07 10 09 58 | G 1/4 male | 41,0            | 13                       | Aluminij            | 5        |
| K- 07 10 09 59 | G 1/4 male | 46,0            | 17                       | Die cast zinc       | 6        |
| K- 07 10 11 14 | G 1/4 male | 40,0            | 17                       | Plastic (POM)       | 7        |
| K- 07 10 11 15 | G 1/4 male | 35,0            | 11                       | Aluminij            | 8        |
| K- 07 10 11 16 | G 1/4 male | 47,0            | 19                       | Die cast zinc       | 9        |
| K- 07 10 11 17 | G 1/4 male | 55,0            | 19                       | Plastic (ABS)       | 10       |