

# K-3/2 ANFAV 24 V DC HW G

Start-up valves, power supply 24 V DC, with »HW« mounting bracket and silencer

**HANSA FLEX**

## Karakteristike

|                              |  |
|------------------------------|--|
| Ulazni tlak                  | 2.5 - 9 bar  |
| Temperatura medija           | max. 70 °C   |
| Okolna temperatura           | Max. 70 °C   |
| Električni priključak        | Coupler plug PG 9 - form B                                     |
| Brtveni materijal            | NBR  |
| Kućište                      | Die-cast aluminium   |
| Mjerenje vrijednosti protoka | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |
| Drugi podatci                | User manual on request   |



## Artikli

| Naziv          | Navoj | Protok (L/min) | A (mm) | B        | C (mm) | D (mm) | Veličina |
|----------------|-------|----------------|--------|----------|--------|--------|----------|
| K- 07 25 12 05 | G 1/4 | 1600           | 65,0   | 131,0 mm | 97,0   | 34,0   | 300      |
| K- 07 25 12 07 | G 3/8 | 2500           | 65,0   | 131,0 mm | 97,0   | 34,0   | 300      |
| K- 07 25 12 09 | G 1/2 | 2500           | 65,0   | 131,0 mm | 97,0   | 34,0   | 300      |
| K- 07 25 12 11 | G 3/8 | 4500           | 78,0   | 142,5 mm | 102,0  | 40,5   | 400      |
| K- 07 25 12 13 | G 1/2 | 4500           | 78,0   | 142,5 mm | 102,0  | 40,5   | 400      |

## Pribor

|                       |                 |
|-----------------------|-----------------|
| K-VERBINDUNGSELEMENTE | Connecting sets |
| K-WANDHALTER          | Wall bracket    |
| K-HALTERBAUSATZ       | Holder          |