

# K-3/2 ABSPERRVENTILE HW SCHL G-MINI

3/2-way shut-off valve

**HANSA FLEX**

## Karakteristike

|                              |  |
|------------------------------|--|
| Ulazni tlak                  | 0 - 9 bar  |
| Temperatura medija           | max. 70 °C   |
| Okolna temperatura           | Max. 70 °C   |
| Odzračni priključak          | G 1/4  |
| Brtveni materijal            | NBR  |
| Kućište                      | Die-cast aluminium   |
| Pritega                      | Plastic  |
| Mjerenje vrijednosti protoka | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |
| Drugi podatci                | User manual on request   |



## Artikl

| Naziv          | Navoj | Protok (L/min) | A (mm) | B       | C (mm) | D (mm) | Veličina |
|----------------|-------|----------------|--------|---------|--------|--------|----------|
| K- 07 25 12 29 | G 1/8 | 1750           | 38,0   | 89,0 mm | 52,5   | 36,5   | 200      |
| K- 07 25 12 30 | G 1/4 | 1750           | 38,0   | 89,0 mm | 52,5   | 36,5   | 200      |

## Pribor

|                       |                 |
|-----------------------|-----------------|
| K-VERBINDUNGSELEMENTE | Connecting sets |
| K-WANDHALTER          | Wall bracket    |
| K-HALTERBAUSATZ       | Holder          |