# K-ENDVERTEILERDOSEN

End porting box without through-hole thread, PN 15

## Karakteristike

| | |
|---|---|
| **Radni tlak** | Max. 15 bar |
| **Okretni moment pričvršćenja** | 4 Nm |
| **Okretni moment MS navoja** | 12 Nm |
| **Temperaturno područje** | -10 °C to +50 °C |
| **Kućište** | Glass fibre-reinforced plastic |
| **Navoj** | Brass |



## Napomena

Drugi podatci na zahtjev.

## Opis

1, 2 or 3-way porting boxes made of high-strength glass fibre-reinforced plastic for a wide range of applications. Available with up to 3 couplings and 2 inlet thread sizes. Optional through-hole thread at the bottom to facilitate the passage of the medium. All porting boxes have a robust, brass threaded insert for high tightening torques, TÜV certified. Suitable for almost any pneumatic application.

## Artikl

| Naziv | Ulaz navoja | Navoj priključka |
|---|---|---|
| **K- 07 40 48 12** | G 1/2" | 1 x G 1/2 |
| **K- 07 40 48 13** | G 1/2" | 2 x G 1/2 |
| **K- 07 40 48 14** | G 1/2" | 3 x G 1/2 |
| **K- 07 40 48 15** | G 3/4" | 1 x G 1/2 |
| **K- 07 40 48 16** | G 3/4" | 2 x G 1/2 |
| **K- 07 40 48 17** | G 3/4" | 3 x G 1/2 |

*Usprkos pažljivoj provjeri ne mogu se isključiti pogreške i zbog toga ne preuzimamo odgovornost za sadržane podatke.*