

# K-SCHUTZROHRE EINSCHRAUB

Screw-in thermowells

**HANSA FLEX**

## Karakteristike

|                    |  |
|--------------------|--|
| Radni tlak         | Max. 6 bar (copper alloy), Max. 25 bar (stainless steel) |
| Ø brtvenog vijenca | 26 mm  |
| Ø zaštitne cijevi  | 10 mm  |
| Materijal          | Copper alloy, CrNi-Steel 1.4571                          |



## Napomena

Drugi podatci na zahtjev.

## Opis

For bimetallic thermometers in the »High quality« series.

## Artikli

| Naziv          | Navoj priključka | Ugradna duljina | SW (mm) | Materijal         |
|----------------|------------------|-----------------|---------|-------------------|
| K- 07 20 11 35 | G 1/2            | L1 = 63 mm      | 27      | Copper alloy      |
| K- 07 20 11 36 | G 1/2            | L1 = 100 mm     | 27      | Copper alloy      |
| K- 07 20 11 37 | G 1/2            | L1 = 160 mm     | 27      | Copper alloy      |
| K- 07 20 11 38 | G 1/2            | L1 = 63 mm      | 27      | CrNi steel 1.4571 |
| K- 07 20 11 39 | G 1/2            | L1 = 100 mm     | 27      | CrNi steel 1.4571 |
| K- 07 20 11 40 | G 1/2            | L1 = 160 mm     | 27      | CrNi steel 1.4571 |

## Pribor

K-BIMETALLTHERMOMETER 52-2 Bimetallic thermometers