

# K-SCHUTZROHRE EINSCHRAUB

Screw-in thermowells

**HANSA FLEX**

## Karakteristike

Radni tlak	Max. 6 bar (copper alloy), Max. 25 bar (stainless steel)
Ø brtvenog vijenca	26 mm
Ø zaštitne cijevi	10 mm
Materijal	Copper alloy, CrNi-Steel 1.4571



## Napomena

Drugi podatci na zahtjev.

## Opis

For bimetallic thermometers in the »High quality« series.

## Artikli

Naziv	Navoj priključka	Ugradna duljina	SW (mm)	Materijal
K- 07 20 11 35	G 1/2	L1 = 63 mm	27	Copper alloy
K- 07 20 11 36	G 1/2	L1 = 100 mm	27	Copper alloy
K- 07 20 11 37	G 1/2	L1 = 160 mm	27	Copper alloy
K- 07 20 11 38	G 1/2	L1 = 63 mm	27	CrNi steel 1.4571
K- 07 20 11 39	G 1/2	L1 = 100 mm	27	CrNi steel 1.4571
K- 07 20 11 40	G 1/2	L1 = 160 mm	27	CrNi steel 1.4571

## Pribor

K-BIMETALLTHERMOMETER 52-2 Bimetallic thermometers