

# K-TR PVC SET

PVC air hose kits

**HANSA FLEX**

## Karakteristike

Radna temperatura od -15 °C do +60 °C



## Napomena

Drugi podatci na zahtjev.

## Opis

Flexible, pressure-resistant and non-abrasive standard hose, also resistant to ageing. Assembled with brass stem and brass quick disconnect coupling DN 7.2.

## Artikli

| Naziv          | Ø crijeva iznutra (mm) | Ø crijeva izvana (mm) | Max. working pressure resistance at 23°C (bar) | Duljina crijeva (m) |
|----------------|------------------------|-----------------------|--|---------------------|
| K- 07 10 12 13 | 6,0                    | 12,0                  | 15   | 5                   |
| K- 07 10 12 09 | 6,0                    | 12,0                  | 15   | 10                  |
| K- 07 10 12 10 | 6,0                    | 12,0                  | 15   | 15                  |
| K- 07 10 12 11 | 6,0                    | 12,0                  | 15   | 20                  |
| K- 07 10 12 12 | 6,0                    | 12,0                  | 15   | 25                  |
| K- 07 10 12 18 | 9,0                    | 15,0                  | 15   | 5                   |
| K- 07 10 12 14 | 9,0                    | 15,0                  | 15   | 10                  |
| K- 07 10 12 15 | 9,0                    | 15,0                  | 15   | 15                  |
| K- 07 10 12 16 | 9,0                    | 15,0                  | 15   | 20                  |
| K- 07 10 12 17 | 9,0                    | 15,0                  | 15   | 25                  |
| K- 07 10 12 08 | 13,0                   | 20,0                  | 15   | 5                   |
| K- 07 10 12 07 | 13,0                   | 20,0                  | 15   | 10                  |