

K-NEBELOELER PC-BEHÄLTER HW G-MINI

Oil-mist lubricators

HANSA FLEX

Karakteristike

| | |
|------------------------------|--|
| Ulazni tlak | Max. 10 bar |
| Temperatura medija | max. 70 °C |
| Okolna temperatura | Max. 70 °C |
| Radni tlak | 0.5 - 9 bar |
| Brtveni materijal | NBR |
| Pokrov s oprugom | POM |
| Kućište | Die-cast aluminium |
| Nastavak za kapanje | Brass/POM |
| Mjerenje vrijednosti protoka | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |
| Drugi podatci | User manual on request |



Artikli

| Naziv | Navoj | Protok (L/min) | A (mm) | B | C (mm) | D (mm) | Veličina |
|----------------|-------|----------------|--------|----------|--------|--------|----------|
| K- 07 25 08 75 | G 1/8 | 1950 | 38,0 | 119,0 mm | 39,0 | 80,0 | 200 |
| K- 07 25 08 76 | G 1/4 | 1950 | 38,0 | 119,0 mm | 39,0 | 80,0 | 200 |

Pribor

| | |
|------------------------------------|---|
| K-ERSATZBEHÄLTER G UND G-MINI POLY | Spare tanks »G« Series and »G-mini« Series Polycarbonat |
| K-HALTERBAUSATZ | Holder |
| K-VERBINDUNGSELEMENTE | Connecting sets |
| K-WANDHALTER | Wall bracket |