



# K-XRD STECKANSCHLUSS Z GEW AGR-K BE

Straight non-return valves, flow direction from tube to port, conical male thread, coated

**HANSA FLEX**

## Karakteristike

Radni tlak	Max. 10 bar, vacuum
Područje primjene	Air, vacuum
preporučena crijeva	PU or PA (nylon)
Mediji	komprimirani zrak
Norma	R thread acc. to ISO 7-1, thread coating
Temperaturno područje	0 °C to +60 °C
Brtvena površina	Conical version: thread coating
Materijal	Plastic, Nickel plated brass
Pritisni prsten	Plastic



## Napomena

Drugi podatci na zahtjev.

## Opis

The non-return function of these push-in fittings prevents the air from flowing back. the unidirectional design means air flow is only possible in one direction. These valves are available with air flow from the port to the tube or from the tube to the port.

## Artikli

Naziv	Navoj	za vanjski Ø crijeva	L1 (mm)	Tlak otvaranja (bar)	SW (veličina ključa)
K- 07 40 08 97	R 1/8	4 mm	24,0	0,2	10 mm
K- 07 40 08 98	R 1/8	6 mm	31,0	0,2	12 mm
K- 07 40 08 99	R 1/8	8 mm	32,8	0,2	14 mm
K- 07 40 08 95	R 1/4	6 mm	33,0	0,2	14 mm
K- 07 40 08 96	R 1/4	8 mm	34,8	0,2	14 mm
K- 07 40 09 00	R 3/8	10 mm	41,0	0,2	17 mm
K- 07 40 09 01	R 3/8	12 mm	42,5	0,2	21 mm
K- 07 40 08 93	R 1/2	10 mm	43,0	0,2	21 mm
K- 07 40 08 94	R 1/2	12 mm	44,5	0,2	21 mm