


K-WV 3/2 5/2 NAMUR LB

3/2 and 5/2-way spool valves with NAMUR style interface

HANSA FLEX

Karakteristike

Mediji	Air, neutral gases (filtered)
Radni tlak	1.5 - 8 bar
Radna temperatura	+5 °C to +50 °C
Električni priključak	Plug connector PG 9
Kućište	Aluminium
Brtnveni materijal	NBR



Napomena

Drugi podatci na zahtjev.

Opis

Pilot-operated 3/2 and 5/2-way spool valves with threaded ports and a NAMUR style interface. Combines high-quality design with a low price. By adding the conversion plate supplied with each valve, the device can be adapted to a 3/2-way function. The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure. Includes a manual operator as standard.

Artikli

Naziv	Napon	Port 1	Priključak 3 + 5	DN	Protok (L/min)
K- 07 15 00 09	230 V, 50 Hz	G 1/4	G 1/4	8	1370
K- 07 15 00 10	24 V DC	G 1/4	G 1/4	8	1370
K- 07 15 00 11	230 V, 50 Hz	G 3/8	G 1/4	10	1650
K- 07 15 00 12	24 V DC	G 3/8	G 1/4	10	1650