


# K-XVMK 5

Male connectors, conical male thread acc. to ISO 7-1, stainless steel

**HANSA FLEX**

## Karakteristike

Područje tlaka	Max. 25 bar
preporučena crijeva	PTFE hose
Temperaturno područje	-40 °C to +200 °C (depending on the hose quality and diameter)
Materijal	Oplemenjeni čelik 1.4404
Brtva	Pure metal



## Napomena

Drugi podatci na zahtjev.

## Opis

Supplied without seals. For use with corrosive media and at high temperatures. Screw fitting series made of stainless steel for all applications where compliance with strict tightness, pressure and temperature requirements is essential. The parts are manufactured without rubber seals, in other words they are ideal for very high temperatures or for use with corrosive liquids, e.g. in cases when FPM is no longer suitable.

## Artikl

Naziv	Navoj	za crijevo	L1 (mm)	SW1 (mm)	SW2 (mm)
K- 07 40 30 19	R 1/8	6 mm / 4 mm	26,0	12	10
K- 07 40 30 20	R 1/8	8 mm / 6 mm	26,5	14	13
K- 07 40 30 17	R 1/4	6 mm / 4 mm	29,5	12	14
K- 07 40 30 18	R 1/4	8 mm / 6 mm	30,0	14	14
K- 07 40 30 16	R 1/4	10 mm / 8 mm	32,5	16	14
K- 07 40 30 21	R 3/8	10 mm / 8 mm	33,0	16	17