

# K-SCHLAUCHTUELLEN KUPP

Hose stems for couplings DN 7.2 - DN 7.8, swivel type, nickel-plated brass / steel, male

**HANSA FLEX**

## Karakteristike

Radni tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
Protok zraka	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura medija	0 °C to +70 °C
Kućište, čahura, tijelo ventila	Nickel-plated brass
Opruga, razorni prsten, kugle	Stainless steel
Brtnveni materijal	NBR



## Napomena

Drugi podatci na zahtjev.

## Artikli

Naziv	Priključak	LW (mm)	Materijal
K- 07 35 02 02	G 1/4 male	6	Nickel-plated brass
K- 07 35 02 03	G 1/4 male	8	Nickel-plated brass
K- 07 35 02 04	G 1/4 male	9	Nickel-plated brass
K- 07 35 02 05	G 1/4 male	10	Nickel-plated brass
K- 07 35 01 78	G 1/4 male	13	Nickel-plated brass
K- 07 35 02 15	R 3/8 male	6	Nickel-plated steel
K- 07 35 02 16	R 3/8 male	9	Nickel-plated steel