
K-VLST L AG IG MS NI

Extensions, long, parallel - nickel-plated brass

Karakteristike

Radna temperatura	Max. 150 °C
Tlak	Max. 60 bar
Materijal	poniklani mjed





Napomena

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.
Drugi podatci na zahtjev.

Opis

Suitable for air, water, oil, steam, etc.

Dodatne informacije

Further types and dimensions on request.

Artikl

Naziv	Vanjski navoj	Unutarnji navoj	L1 (mm)	SW (veličina ključa)
K- 07 40 39 16	G 1/8	G 1/8	22,0	14 mm
K- 07 40 39 17	G 1/8	G 1/8	42,0	14 mm
K- 07 40 39 18	G 1/8	G 1/8	51,0	14 mm
K- 07 40 39 19	G 1/8	G 1/8	100,0	14 mm
K- 07 40 39 20	G 1/4	G 1/4	35,0	17 mm
K- 07 40 39 21	G 1/4	G 1/4	51,0	17 mm
K- 07 40 39 22	G 1/4	G 1/4	100,0	17 mm

Usprkos pažljivoj provjeri ne mogu se isključiti pogreške i zbog toga ne preuzimamo odgovornost za sadržane podatke.