

K-DROSSELPLATT NAMUR VENTIL

Flow regulators for NAMUR valves

HANSA FLEX

Karakteristike

Mediji	Air, neutral gases, filtered
Radni tlak	0.5 to 10 bar
Radna temperatura	-20 °C to +70 °C
Sadržano u opsegu isporuke	1 coding pin (not for K-07152240), 2 O-rings, 2 fixing screws
Kućište	Aluminium, anodised
Materijal	Brтва: NBR
Brtveni materijal	NBR



Napomena

Drugi podatci na zahtjev.

Opis

Block-form flow regulator as an intermediate plate between the control valve and actuator acc. to the G 1/4 NAMUR standard. 3/2-way flow regulators: Independent regulation of the forward and return strokes of a single-acting pneumatic actuator. 5/2-way flow regulators: Regulation of the forward and return strokes of a double-acting pneumatic actuator.

Artikl

Naziv	Funkcija	Aktiviranje	DN	Protok (L/min)
K- 07 15 22 39	3/2-way	Knurled Screw	5	650
K- 07 15 22 40	3/2-way	Screwdriver	5	650
K- 07 15 22 41	5/2-way	Knurled Screw	5	650
K- 07 15 22 42	5/2-way	Screwdriver	5	650