

# K-BKR SCHW STAHLHEBEL IG AG

Ball valves with black steel lever, lightweight type, female/male thread

**HANSA FLEX**

## Karakteristike

|                          |  |
|--------------------------|--|
| <b>Područje primjene</b> | Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture   |
| <b>Radni tlak</b>        | Max. 40 bar  |
| <b>Radna temperatura</b> | -15 °C to +90 °C   |
| <b>Opis navoja</b>       | G thread acc. DIN EN ISO 228-1   |
| <b>Kućište</b>           | Nickel-plated brass  |
| <b>Poluga</b>            | Steel, with plastic coating  |
| <b>Kugla</b>             | Chrome-plated brass  |
| <b>Brtva kugle</b>       | PTFE   |
| <b>Brtva vretena</b>     | HNBR / EPDM / PTFE. 2 O-Rings (HNBR / EPDM)<br>1 gasket (PTFE)<br>additional PTFE-gasket |



## Napomena

Drugi podatci na zahtjev.

## Artikli

| Naziv          | DN | Navoj   | A<br>(mm) | B<br>(mm) | L<br>(mm) |
|----------------|----|---------|-----------|-----------|-----------|
| K- 07 30 00 51 | 8  | G 1/4   | 85,0      | 42,0      | 44,0      |
| K- 07 30 00 55 | 10 | G 3/8   | 85,0      | 42,0      | 51,0      |
| K- 07 30 00 59 | 15 | G 1/2   | 85,0      | 46,0      | 60,0      |
| K- 07 30 00 63 | 20 | G 3/4   | 105,0     | 53,0      | 70,0      |
| K- 07 30 00 67 | 25 | G 1     | 105,0     | 57,0      | 79,0      |
| K- 07 30 00 71 | 32 | G 1 1/4 | 130,0     | 70,0      | 91,0      |
| K- 07 30 00 75 | 40 | G 1 1/2 | 130,0     | 76,0      | 104,0     |
| K- 07 30 00 79 | 50 | G 2     | 165,0     | 92,0      | 122,0     |