

K-DMUF 1

Pressure transmitters (CrNi steel 1.4404)

HANSA FLEX

Karakteristike

| | |
|--|--|
| Tip | A-10 |
| Napon | 8 - 30 V |
| Električni priključak | With right-angle connector acc. to DIN EN 175301-803 A |
| Vrsta zaštite | IP 65 acc. to EN 60529 |
| Izlazni signal | 4 to 20 mA, 2-wire |
| Nelinearnost | 0.5% of span |
| Temperatura medija | 0 °C to +80 °C |
| Okolna temperatura | 0 °C to +80 °C |
| Dijelovi koji dolaze u dodir s mjernom tvari | CrNi steel 1.4404 |
| Kućište | CrNi steel 1.4404 |



Napomena

Drugi podatci na zahtjev.

Opis

Standard type for universal applications. Suitable for electronic pressure measurements in the low and high-pressure ranges.

Dodatne informacije

Further measuring ranges on request

Pressure converter with output signal 0 - 10 V, 0 - 5 V and others on request.

Artikli

| Naziv | Mjerno područje | Navoj |
|----------------|-----------------|-------|
| K- 07 20 10 46 | 0 - 1.0 bar | G 1/4 |
| K- 07 20 10 47 | 0 - 1.6 bar | G 1/4 |
| K- 07 20 10 48 | 0 - 2.5 bar | G 1/4 |
| K- 07 20 10 49 | 0 - 4.0 bar | G 1/4 |
| K- 07 20 10 50 | 0 - 6.0 bar | G 1/4 |
| K- 07 20 10 51 | 0 - 10.0 bar | G 1/4 |
| K- 07 20 10 52 | 0 - 16.0 bar | G 1/4 |
| K- 07 20 10 53 | 0 - 25.0 bar | G 1/4 |
| K- 07 20 10 54 | 0 - 40.0 bar | G 1/4 |
| K- 07 20 10 55 | 0 - 60.0 bar | G 1/4 |
| K- 07 20 10 56 | 0 - 100.0 bar | G 1/4 |
| K- 07 20 10 57 | 0 - 160.0 bar | G 1/4 |
| K- 07 20 10 58 | 0 - 250.0 bar | G 1/4 |
| K- 07 20 10 59 | 0 - 400.0 bar | G 1/4 |
| K- 07 20 10 60 | 0 - 600.0 bar | G 1/4 |