

K-SVKM NW 7,2 DREH MS-NI

Quick disconnect couplings DN 7.2, nickel-plated brass, swivel type

HANSA FLEX

Karakteristike

Radni tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
Protok zraka	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura medija	0 °C to +70 °C
Kućište, čahura	Nickel-plated brass
Ventil	Brass with a bare metal surface
Opruga, razorni prsten	Stainless steel 1.4310
Zatoci za zaključavanje	Stainless steel 1.4034
Brtveni materijal	NBR



Napomena

Drugi podatci na zahtjev.

Opis

Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

Artikli

Naziv	Priključak	Duljina (mm)
K- 07 35 07 28	Stem 6 mm, swivel type	74,0
K- 07 35 07 29	Stem 8 mm, swivel type	74,0
K- 07 35 07 30	Stem 9 mm, swivel type	74,0
K- 07 35 07 31	Stem, 10 mm, swivel type	74,0
K- 07 35 07 32	Stem, 13 mm, swivel type	74,0

Dodatni elementi

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass