


K-NIPPEL KUPPL NW7 AG MS NI

Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male

HANSA FLEX

Karakteristike

Radni tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
Temperatura medija	-20 °C to +100 °C
Materijal	poniklani mjed



Napomena

Drugi podatci na zahtjev.

Artikli

Naziv	Definicija	SW (mm)
K- 07 35 01 92	Plug G 1/8 male	14
K- 07 35 01 93	Plug G 1/4 male	17
K- 07 35 01 94	Plug G 3/8 male	19
K- 07 35 01 95	Plug G 1/2 male	24

je dodatni element uz sljedeće proizvode

K-SVKM NW 7,8 AG H	Quick disconnect couplings DN 7.8 - for extremely high flow rates, male
K-SVKM NW 7,8 IG H	Quick disconnect couplings DN 7.8 - for extremely high flow rates, female
K-SVKM NW 7,8 SCHL TUE H	Quick disconnect couplings DN 7.8 - for extremely high flow rates, with hose stem
K-LKM S NW7,8 AG	Safety couplings DN 7.8, male
K-LKM S NW7,8 IG	Safety couplings DN 7.8, female
K-LKM S NW7,8 SCHL TUE	Safety couplings DN 7.8, with hose stem