

K-SVKM NW 7,2 AG VA

Quick disconnect couplings DN 7.2, stainless steel, male

HANSA FLEX

Karakteristike

Radni tlak	1 - 35 bar and rough vacuum
Protok zraka	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura medija	-25 °C to +200 °C
Kućište, čahura, tijelo ventila	Stainless steel 1.4305
Opruga, razorni prsten	Stainless steel 1.4310
Zatici za zaključavanje	Stainless steel 1.4401
Brtveni materijal	FKM



Napomena

Drugi podatci na zahtjev.

Opis

Classic standard coupling type, one side sealing, made of stainless steel. The closed sleeve protects the coupling from dirt. We recommend the use of stainless steel plugs and stems!

Artikli

Naziv	Priključak	Duljina (mm)	SW (mm)
K- 07 35 07 59	G 1/4 male	43,0	22
K- 07 35 07 60	G 3/8 male	43,0	22
K- 07 35 07 61	G 1/2 male	46,0	24

Dodatni elementi

K-NIPPEL KUPPL NW7 AG VA 2	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, male
K-NIPPEL KUPPL NW7 IG VA 1	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, female
K-TUE 7,2 7,8 VA 2	Stems for couplings DN 7.2 - DN 7.8, stainless steel 1.4305