

K-SVKM NW 7,8 IG H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, female

HANSA FLEX

Karakteristike

Radni tlak	0 - 35 bar
Protok zraka	2.100 l/min (at $\Delta p = 0.5$ bar)
Temperatura medija	-20 °C to +40 °C
Navojni element	Nickel-plated brass
Tijelo ventila	Steel, QPQ treated
Deblokirajuća čahura	Extremely robust, ergonomic plastic
Ventil, dosjed	Brass
Mediji	Only for clean compressed air
Brtve	NBR
Opruga, razorni prsten, kugle	stain less steel



Napomena

Drugi podatci na zahtjev.

Opis

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

Artikli

Naziv	Priključak	Duljina (mm)	SW (mm)
K- 07 35 08 50	G 1/4 female	59,0	19
K- 07 35 08 51	G 3/8 female	59,0	19
K- 07 35 08 52	G 1/2 female	62,0	24

Dodatni elementi

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass