

K-LKM S NW7,8 SCHL TUE

Safety couplings DN 7.8, with hose stem

HANSA FLEX

Karakteristike

| | |
|---------------------------|---|
| Radni tlak | maks. 20 bar |
| Protok zraka | 1.400 l/min (at 6 bar and $\Delta p = 0.5$ bar) |
| Temperatura medija | -20 °C to +100 °C |
| Priključak tijela ventila | Nickel-plated brass |
| Opruga, kugle | Stainless-steel |
| Klizna čahura | Anodised aluminium |
| Deblokirajuća čahura | Hardened and nickel-plated steel |
| Brtveni materijal | NBR |



Napomena

Drugi podatci na zahtjev.

Opis

Safety air relief couplings for gaseous media. Combination of a sliding valve and a quick disconnect coupling! Connection is pressureless. Only a low spring force has to be overcome. Pressure only builds up when the blue sleeve is pushed forward. It is impossible to disconnect the hose either intentionally or inadvertently in this position. When the sliding sleeve is moved back into its home position, the air is relieved from the hose and the coupling can be disconnected.

Artikli

| Naziv | Priključak | Duljina (mm) |
|----------------|---------------|--------------|
| K- 07 35 08 88 | Stem, I.D. 6 | 86,0 |
| K- 07 35 12 96 | Stem, I.D. 8 | 86,0 |
| K- 07 35 08 89 | Stem, I.D. 9 | 86,0 |
| K- 07 35 12 97 | Stem, I.D. 10 | 86,0 |
| K- 07 35 08 90 | Stem, I.D. 13 | 86,0 |

Dodatni elementi

| | |
|-------------------------------|--|
| K-NIPP KUPPL NW7 SCHL MS NI K | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring |
| K-NIPPEL KUPPL NW7 AG MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male |
| K-NIPPEL KUPPL NW7 IG MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female |
| K-NIPPEL KUPPL NW7 SCHL MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose |
| K-TUE 5 MS NI | Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass |