

# K-PRAEZI DRUCKREGL OHNE EIGENLUF

Precision pressure regulators without air consumption

**HANSA FLEX**

## Karakteristike

|                          |                                                                  |
|--------------------------|------------------------------------------------------------------|
| Ulazni tlak              | Max. 16 bar                                                      |
| Temperatura medija       | max. 80 °C                                                       |
| Okolna temperatura       | Max. 80 °C                                                       |
| Mediji                   | Fine-filtered (5 µm), unlubricated compressed air, neutral gases |
| Priključak za manometar  | G 1/4                                                            |
| Brtnveni materijal       | NBR                                                              |
| Kućište                  | Die-cast zinc                                                    |
| Stožac ventila, membrana | FPM                                                              |



## Napomena

Drugi podatci na zahtjev.

## Opis

Diaphragm pressure regulators with self-relieving design for applications requiring an accurate working pressure.

## Artikli

| Naziv          | Navoj | Regulacijsko područje | Protok (L/min) | A (mm) | B        | C (mm) | D (mm) |
|----------------|-------|-----------------------|----------------|--------|----------|--------|--------|
| K- 07 25 09 39 | G 1/4 | 0 - 1 bar             | 600            | 82,0   | 148,0 mm | 19,5   | 128,5  |
| K- 07 25 09 40 | G 1/4 | 0.1 - 3 bar           | 760            | 82,0   | 148,0 mm | 19,5   | 128,5  |
| K- 07 25 09 41 | G 1/4 | 0.2 - 6 bar           | 550            | 82,0   | 148,0 mm | 19,5   | 128,5  |
| K- 07 25 09 42 | G 1/4 | 0.5 - 10 bar          | 400            | 82,0   | 148,0 mm | 19,5   | 128,5  |

## Pribor

K-HALTERBAUSATZ STANDARD Holder