

# K-ROHRDOPPELNIPPEL MS

Double pipe nipples, brass

**HANSA FLEX**

## Karakteristike

|                    |                                 |
|--------------------|---------------------------------|
| Radni tlak         | 10 bar                          |
| Temperatura medija | max. 90 °C                      |
| Okolna temperatura | Max. 90 °C                      |
| Navoj priključka   | R-thread to EN 10226            |
| Materijal          | Brass with a bare metal surface |



## Napomena

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.

Drugi podatci na zahtjev.

## Artikli

| Naziv          | Navoj   | Duljina (mm) |
|----------------|---------|--------------|
| K- 07 40 16 25 | G 1/2   | 30,0         |
| K- 07 40 16 26 | G 1/2   | 40,0         |
| K- 07 40 16 27 | G 1/2   | 50,0         |
| K- 07 40 16 28 | G 1/2   | 60,0         |
| K- 07 40 16 29 | G 1/2   | 80,0         |
| K- 07 40 16 20 | G 1/2   | 100,0        |
| K- 07 40 16 21 | G 1/2   | 120,0        |
| K- 07 40 16 22 | G 1/2   | 150,0        |
| K- 07 40 16 23 | G 1/2   | 180,0        |
| K- 07 40 16 24 | G 1/2   | 200,0        |
| K- 07 40 16 41 | G 3/4   | 40,0         |
| K- 07 40 16 42 | G 3/4   | 60,0         |
| K- 07 40 16 43 | G 3/4   | 80,0         |
| K- 07 40 16 36 | G 3/4   | 100,0        |
| K- 07 40 16 37 | G 3/4   | 120,0        |
| K- 07 40 16 38 | G 3/4   | 150,0        |
| K- 07 40 16 39 | G 3/4   | 180,0        |
| K- 07 40 16 40 | G 3/4   | 200,0        |
| K- 07 40 16 04 | G 1     | 40,0         |
| K- 07 40 16 05 | G 1     | 60,0         |
| K- 07 40 16 06 | G 1     | 80,0         |
| K- 07 40 15 99 | G 1     | 100,0        |
| K- 07 40 16 00 | G 1     | 120,0        |
| K- 07 40 16 01 | G 1     | 150,0        |
| K- 07 40 16 02 | G 1     | 180,0        |
| K- 07 40 16 03 | G 1     | 200,0        |
| K- 07 40 16 18 | G 1 1/4 | 60,0         |
| K- 07 40 16 19 | G 1 1/4 | 80,0         |
| K- 07 40 16 13 | G 1 1/4 | 100,0        |
| K- 07 40 16 14 | G 1 1/4 | 120,0        |
| K- 07 40 16 15 | G 1 1/4 | 150,0        |
| K- 07 40 16 16 | G 1 1/4 | 180,0        |
| K- 07 40 16 17 | G 1 1/4 | 200,0        |
| K- 07 40 16 11 | G 1 1/2 | 60,0         |
| K- 07 40 16 12 | G 1 1/2 | 80,0         |
| K- 07 40 16 07 | G 1 1/2 | 100,0        |
| K- 07 40 16 08 | G 1 1/2 | 120,0        |
| K- 07 40 16 09 | G 1 1/2 | 150,0        |
| K- 07 40 16 10 | G 1 1/2 | 200,0        |
| K- 07 40 16 34 | G 2     | 60,0         |
| K- 07 40 16 35 | G 2     | 80,0         |
| K- 07 40 16 30 | G 2     | 100,0        |
| K- 07 40 16 31 | G 2     | 120,0        |
| K- 07 40 16 32 | G 2     | 150,0        |
| K- 07 40 16 33 | G 2     | 200,0        |