

# K-ZFL VENTILINSEL HDM

Intermediate plates for HDM valve terminal

## Karakteristike

<b>Mediji</b>	Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
<b>Radni tlak</b>	Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)
<b>Upravljački tlak</b>	3 - 7 bar
<b>Temperaturno područje</b>	-10 °C to +60 °C
<b>Protok</b>	200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8)
<b>Broj aktiviranja</b>	Max. 16 (e.g. 16 spring return valves)
<b>Pomoćno ručno aktiviranje</b>	Latching (bistable), Monostable (non-latching) version also available on request
<b>Potrošnja struje</b>	0.6 W per pilot
<b>Vrsta zaštite</b>	IP 65



## Napomena

Drugi podatci na zahtjev.

## Opis

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

## Dodatne informacije

Important: The scope of supply does not include a connector. Please order separately.

## Artikl

Naziv	Funkcija
K- 07 15 22 51	With additional pilots and exhausts
K- 07 15 22 52	With separate pilots (for multi-pressure systems)
K- 07 15 22 44	With separate exhausts (for multi-pressure system)