

K-ENDPLATTEN V

End plate for HDM valve terminal

Karakteristike

Mediji	Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
Radni tlak	Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)
Upravljački tlak	3 - 7 bar
Temperaturno področje	-10 °C to +60 °C
Protok	200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8)
Broj aktiviranja	Max. 16 (e.g. 16 spring return valves)
Funkcija	Blind (terminates the system)
Pomočno ručno aktiviranje	Latching (bistable), Monostable (non-latching) version also available on request
Potrošnja struje	0.6 W per pilot
Vrsta zaštite	IP 65



Napomena

Drugi podatki na zahtjev.

Opis

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Dodatne informacije

Important: The scope of supply does not include a connector. Please order separately.

Artikl

Naziv	Funkcija
K- 07 15 22 50	Blind (terminates the system)