

# K-L-STECKVER L DREH AG OR

Male elbows, long, swivel type, parallel male thread with O-ring

**HANSA FLEX**

## Karakteristike

|                       |  |
|-----------------------|--|
| Radni tlak            | Max. 15 bar, coarse vacuum   |
| Područje primjene     | Air, vacuum  |
| preporučena crijeva   | PU or PA (nylon)   |
| Mediji                | Compressed air and all gases or liquids that are compatible with the materials |
| Temperaturno područje | -20 °C to +80 °C   |
| Brtvena površina      | Parallel version: O-ring in housing  |
| Materijal             | Plastic, Nickel plated brass   |
| Pritisni prsten       | Plastic  |



## Napomena

Drugi podatci na zahtjev.

## Opis

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Artikli

| Naziv          | Navoj | za vanjski Ø crijeva | L1<br>(mm) | L2<br>(mm) | SW (veličina ključa) |
|----------------|-------|----------------------|------------|------------|----------------------|
| K- 07 40 01 76 | M 5   | 4 mm                 | 18,8       | 32,5       | 8 mm                 |
| K- 07 40 01 77 | M 5   | 6 mm                 | 20,0       | 33,5       | 8 mm                 |
| K- 07 40 01 90 | G 1/8 | 4 mm                 | 18,8       | 30,5       | 14 mm                |
| K- 07 40 01 91 | G 1/8 | 6 mm                 | 20,0       | 31,5       | 14 mm                |
| K- 07 40 01 92 | G 1/8 | 8 mm                 | 22,5       | 37,8       | 14 mm                |
| K- 07 40 01 88 | G 1/8 | 10 mm                | 26,9       | 45,4       | 17 mm                |
| K- 07 40 01 89 | G 1/8 | 12 mm                | 28,5       | 46,9       | 17 mm                |
| K- 07 40 01 85 | G 1/4 | 4 mm                 | 18,8       | 30,5       | 17 mm                |
| K- 07 40 01 86 | G 1/4 | 6 mm                 | 20,0       | 31,5       | 17 mm                |
| K- 07 40 01 87 | G 1/4 | 8 mm                 | 22,5       | 33,8       | 17 mm                |
| K- 07 40 01 83 | G 1/4 | 10 mm                | 26,9       | 46,4       | 17 mm                |
| K- 07 40 01 84 | G 1/4 | 12 mm                | 28,5       | 47,9       | 17 mm                |
| K- 07 40 01 96 | G 3/8 | 6 mm                 | 20,0       | 32,6       | 20 mm                |
| K- 07 40 01 97 | G 3/8 | 8 mm                 | 22,5       | 34,9       | 20 mm                |
| K- 07 40 01 93 | G 3/8 | 10 mm                | 26,9       | 43,4       | 20 mm                |
| K- 07 40 01 94 | G 3/8 | 12 mm                | 28,5       | 44,9       | 20 mm                |
| K- 07 40 01 95 | G 3/8 | 16 mm                | 33,5       | 58,2       | 20 mm                |
| K- 07 40 01 81 | G 1/2 | 6 mm                 | 20,0       | 33,3       | 24 mm                |
| K- 07 40 01 82 | G 1/2 | 8 mm                 | 22,5       | 37,3       | 24 mm                |
| K- 07 40 01 78 | G 1/2 | 10 mm                | 26,9       | 45,3       | 24 mm                |
| K- 07 40 01 79 | G 1/2 | 12 mm                | 28,5       | 46,8       | 24 mm                |
| K- 07 40 01 80 | G 1/2 | 16 mm                | 33,5       | 54,9       | 24 mm                |